

PACER™



Product Specifications



APPLICATION:	For all types of gasoline dispensing applications where flexibility and a lightweight hose is desired. Pacer™ is designed with a spiral textile reinforcement. UL 330 and CUL approved.
CONSTRUCTION	
TUBE:	Nitrile synthetic rubber (ORS)
COVER:	Chemivic™ synthetic rubber (ORS)
REINFORCEMENT:	Spiral synthetic yarn with static wire
TEMPERATURE:	-40°F to 140°F (-40°C to 60°C)
PACKAGING:	Reels or coupled lengths
BRANDING:	Example: 3/4" Pacer™ Goodyear®
COUPLINGS:	Contact fitting manufacturer for proper fitting recommendation and coupling procedure.
NON-STOCK/SIZES:	For special production run minimum requirements, see Appendix D.
ORDER CODES:	595-015 (bulk) 595-017 (factory coupled assemblies)

PACER™

ID		NOM. OD		WEIGHT	
in.	mm.	in.	mm.	lb./ft.	kg./m.
5/8	15.9	0.98	24.9	0.28	0.42
3/4	19.1	1.15	29.2	0.37	0.55
1	25.4	1.50	38.1	0.60	0.89

AIR &
MULTIPURPOSE
General Purpose
Heavy Duty
Push-on

CHEMICAL
TRANSFER

CLEANING
EQUIPMENT

FOOD
Transfer
Washdown

MARINE

MATERIAL
HANDLING
Abrasives
Bulk Transfer
Cement & Concrete

MINING

PETROLEUM
Aircraft Fueling
Dispensing
Dock
Transfer

SPRAY

STEAM

VACUUM

VEYANCE

WATER
Discharge
Suction &
Discharge
Washdown

WELDING

COUPLING
SYSTEMS

APPENDIX