



Prospector™ Hot Oiler

This hose is designed for static-pressure, Hot Oiler applications. It is made specifically to handle the transfer of hot oil at 275°F continuous and 300°F intermittent to clear the paraffin around the casing to help start the flow of oil to the surface.

Performance + Specs

- Meets Flame Resistance
 - USMSHA Designation
- Inner Tube
 - Oil Resistant Synthetic Rubber Black
- Reinforcement
 - Two braids of high-tensile steel wire
- Cover
 - Oil-Resistant Synthetic Rubber (Pin-Pricked) Black
- Temperature Range
 - 40°F / -40°C ~ 275°F / 135°C

Key Features

- ✓ 4:1 Safety Factor
- ✓ Extended Life™ Cover
- ✓ High Temperature

Branding

Prospector™ X-Life HOT OILER 1 ½" 2500 PSI Flame Resistant MSHA 2g-1c-14c/45

Prospector™ Hot Oiler

Product Numbers

SAP	Product #	ID	ID	OD	Max Working Pressure		Bend Radius		MIN BURST Pressure		Fitting Type	Weight (lb/ft)		
		Fraction	in.	mm.	in.	mm.	PSI	MPa	in.	mm.	PSI	Mpa		
20830012	HOT OILER	1 1/2	1.50	38.00	2.16	54.80	2500	17.2	20.00	508.00	8750	60.30	B2	1.64

No Fittings Found