



Saflex® (NSFX)

Saflex® NSFX is designed for medium-pressure applications where shock hazards exist and non-conductivity is required. This hose meets the maximum leakage of 100 microamps/ft. at 75 KV for 3 minutes.

Performance + Specs

- Inner Tube
CR (Polychloroprene) White
- Reinforcement
Two textile braids
- Cover
NBR / PVC (Nitrile / PVC) Orange
- Temperature Range
-40°F / -40°C ~ 212°F / 100°C

Key Features

- 4:1 Safety Factor
- Non-Conductive

Branding

NSFX-08 Saflex® (Non-Conductive) 1/2" (12.7 MM) 2000 PSI (13.8 MPa)

Saflex® (NSFX)

Product Numbers														
SAP	Product #	ID	ID	OD		Max Working Pressure		Bend Radius		MIN BURST Pressure		Fitting Type	Weight (lb/ft)	
		Fraction	in.	mm.	in.	mm.	PSI	MPa	in.	mm.	PSI	Mpa		
20240284	NSFX-06	3/8	0.38	9.50	0.75	19.00	2250	15.5	4.00	102.00	9000	62.10	SF	0.19
20240285	NSFX-08	1/2	0.50	12.70	0.94	23.70	2000	13.8	6.00	152.00	8000	55.20	SF	0.27