



SFS Fire Suppression

SFS

SFS is made for medium-pressure hydraulic applications including fire suppression actuation equipment where the red cover allows for easy identification.

Performance + Specs

Meets Flame Resistance

- **USMSHA Designation**

Inner Tube

Nitrile (NBR) Black

Reinforcement

One braid of high-tensile steel wire

Cover

NBR / PVC (Nitrile / PVC) red Red

Temperature Range

-40°F / -40°C ~ 212°F / 100°C

Key Features

4:1 Safety Factor

Flame Resistance

Branding

SFS-08 Fire Suppression Hose 1/2" (DN12) 2000 PSI 13.8 MPa MSHA 2G-1C-14C/31 MADE IN USA

SFS

Product Numbers

SAP	Product #	ID	ID		OD		Max Working Pressure		Bend Radius		MIN BURST Pressure		Fitting Type	Weight (lb/ft)
		Fraction	in.	mm.	in.	mm.	PSI	MPa	in.	mm.	PSI	Mpa		
20276330	SFS-04	1/4	0.25	6.00	0.53	13.60	2750	19	4.00	102.00	11000	75.80	B2	0.15
20276331	SFS-06	3/8	0.38	10.00	0.69	17.50	2250	15.5	5.00	127.00	9000	62.10	B2	0.22
20276332	SFS-08	1/2	0.50	12.00	0.81	20.70	2000	13.8	7.00	178.00	8000	55.20	B2	0.28
20276333	SFS-12	3/4	0.75	19.00	1.10	27.80	1250	8.6	9.50	241.00	5000	34.20	B2	0.41
20276334	SFS-16	1	1.00	25.00	1.41	35.80	1000	6.9	12.00	305.00	4000	27.60	B2	0.62