



SHJ Jack Hose

SHJ is designed for extreme high-pressure hydraulic lines for jacking systems.

Performance + Specs

- Meets flame resistance
 - **USMSHA Designation**
 - 2:1 Safety Factor
- Inner Tube**
Nitrile (NBR) Black
- Reinforcement**
Two braids of high-tensile steel wire
- Cover**
CR (Polychloroprene) Black
- Temperature Range**
-40°F / -40°C ~ 212°F / 100°C

Key Features

Flame Resistance

Branding

SHJ-04 Jack Hose 1/4" (6.4 MM) 10000 PSI (68.9 MPa) MSHA 2G-14C/12 MADE IN USA

SHJ Jack Hose

Product Numbers

SAP	Product #	ID	ID	OD		Max Working Pressure		Bend Radius		MIN BURST Pressure		Fitting Type	Weight (lb/ft)	
		Fraction	in.	mm.	in.	mm.	PSI	MPa	in.	mm.	PSI	Mpa		
20319601	SHJ-04	1/4	0.25	6.40	0.58	14.70	10000	68.9	4.00	102.00	20000	137.90	B2	0.24
20319602	SHJ-06	3/8	0.38	9.50	0.74	18.70	10000	68.9	5.00	127.00	20000	137.90	B2	0.3