



SR15

SR15 is designed specifically to handle severe-high-pressure applications where pressure spikes or constant hydrostatic loads are present.

Performance + Specs

Meets or exceeds the performance requirements of:

- **SAE 100R15**

Meets Flame Resistance

- **USMSHA Designation**

ABS Type Pending

Inner Tube

CR (Polychloroprene) Black

Reinforcement

Four alternating layers of spiraled high-tensile s

Cover

CR (Polychloroprene) Black

Temperature Range

-40°F / -40°C ~ 250°F / 121°C

Key Features

- 4:1 Safety Factor
- SAE J1942/ U.S. Coast Guard

Branding

SR1SN-08 SAE 100R1AT / 1SN 1/2" (DN12) 2320 PSI (16 MPa) MSHA 2G-14C/12 MADE IN USA

SR15

Product Numbers

SAP	Product #	ID	ID	OD	Max Working Pressure	Bend Radius	MIN BURST Pressure	Fitting Type	Weight (lb/ft)					
		Fraction	in.	mm.	in.	mm.	PSI	MPa	in.	mm.	PSI	Mpa		
20714798	SR15-08	1/2	0.50	12.70	0.95	24.20	6100	42.0	7.90	200.00	24400	165.50	N/A	0.59
20714785	SR15-12	3/4	0.75	19.00	1.26	32.00	6100	42.0	10.40	265.00	24400	165.50	SG	1.09
20714793	SR15-16	1	1.00	25.40	1.53	38.80	6100	42.0	13.00	330.00	24400	165.50	SG	1.46
20714794	SR15-20	1-1/4	1.25	31.80	1.89	48.00	6100	42.0	17.50	445.00	24400	165.50	SG	2.41
20714795	SR15-24	1-1/2	1.50	38.10	2.23	56.80	6100	42.0	20.90	530.00	24400	165.50	DG	3.02