

Continental

X-LIFE™

XCP3S

X-Life™ XCP3S

X-LIFE™XCP3S is made for high-pressure hydraulic applications requiring extra abrasion resistance. This hose has excellent impulse performance and flexibility.

Performance + Specs

Meets Flame Resistance

- **USMSHA Designation**

Meets or Exceeds

- **SAE 100R12**

Color-coded layline system

to identify pressure differences

Inner Tube

Synthetic Rubber Black

Reinforcement

Four alternating layers of spiraled high-tensile w

Cover

Synthetic Rubber BLK Black

Temperature Range

-40°F / -40°C ~ 250°F / 121°C

Key Features

- ✓ 1/2 Bend Radius
- ✓ 4:1 Safety Factor
- ✓ Extended Life™ Cover
- ✓ Handles Constant Pressure
- ✓ SAE J1942/ U.S. Coast Guard

Branding

X-Life™ XCP3S-20 SAE 100R12 1 1/4" (R12) 3100 PSI 21 MPa 213.73 BAR Flame Resistant MSHA 2G-1C-14C/45

X-Life™ XCP3S

Product Numbers

SAP	Product #	ID	ID		OD		Max Working Pressure		Bend Radius		MIN BURST Pressure		Fitting Type	Weight (lb/ft)
		Fraction	in.	mm.	in.	mm.	PSI	MPa	in.	mm.	PSI	Mpa		
20901269	XCP3S-20	1-1/4	1.24	31.50	1.85	47.00	3100	21	16.50	420.00	12400	84.00	SG	1.7
20921133	XCP3S-24	1 1/2	1.50	38.00	2.11	53.50	3100	21	19.60	500.00	12400	84.00	SG	2.05
20921137	XCP3S-32	2	2.00	51.00	2.63	66.70	3100	21	24.80	630.00	12400	84.00	SG	2.82