

X-Life™ XCP4

X-LIFE™XCP4 is made for very high-pressure hydraulic applications requiring extra abrasion resistance. This hose has excellent impulse performance and flexibility.

Performance + Specs

Meets or exceeds the performance requirements of:

- SAE 100R19
- ISO-18752 AC

Meets Flame Resistance

- USMSHA Designation
- SAE J1942 / U.S. Coast Guard

US Coast Guard Approved for sizes 1/4" – 3/4";
Pending US Coast Guard Approval for size 1"

Inner Tube

Nitrile (NBR) Black

Reinforcement

Two braids of high-tensile steel wire

Cover

Synthetic Rubber Black

Temperature Range

-40°F / -40°C ~ 212°F / 100°C

Key Features

4:1 Safety Factor

Extended Life™ Cover

Handles Constant Pressure

SAE J1942/ U.S. Coast Guard

Branding

X-Life™ | XCP4-08 | 4060 PSI | SAE 100R19 1/2" [DN12] ISO-18752/AC | 28.0 MPa 280 BAR | MSHA 2G-IC-14C/37 | B2 | MADE IN USA |

X-Life™ XCP4

Product Numbers

SAP	Product #	ID	ID		OD		Max Working Pressure		Bend Radius		MIN BURST Pressure		Fitting Type	Weight (lb/ft)
		Fraction	in.	mm.	in.	mm.	PSI	MPa	in.	mm.	PSI	Mpa		
20827919	XCP4-04	1/4	0.25	6.40	0.54	13.80	4060	28	2.00	51.00	16240	112.00	B2	0.26
20826087	XCP4-06	3/8	0.38	9.50	0.69	17.60	4060	28	2.50	64.00	16240	112.00	B2	0.3
20828100	XCP4-08	1/2	0.50	12.70	0.82	20.90	4060	28	3.50	88.90	16240	112.00	B2	0.42
20828101	XCP4-10	5/8	0.63	15.90	0.95	24.20	4060	28	4.00	102.00	16240	112.00	B2	0.48
20826123	XCP4-12	3/4	0.75	19.00	1.14	29.00	4060	28	5.00	127.00	16240	112.00	B2	0.66
21191760	XCP4-16	1	1.00	25.45	1.44	36.58	4060	28	5.90	150.00	16240	112.00	B2	1.04