

Continental

X-LIFE™

XCP5S

X-Life™ XCP5S

X-LIFE™XCP5S is made for very high-pressure hydraulic applications requiring extra abrasion resistance. This hose has excellent impulse performance and flexibility.

Performance + Specs

Meets Flame Resistance

- **USMSHA Designation**

Meets or Exceeds

- **SAE 100R13**

Color-coded layline system

to identify pressure differences

Inner Tube

Synthetic Rubber Black

Reinforcement

4 or 6 alternating layers of spiraled high-tensile steel wire

Cover

Synthetic Rubber BLK Black

Temperature Range

-40°F / -40°C ~ 250°F / 121°C

Key Features

1/2 Bend Radius

4:1 Safety Factor

Extended Life™ Cover

Handles Constant Pressure

SAE J1942/ U.S. Coast Guard

Branding

Continental X-Life™ XCP5S-08 SAE 100R13/EN 856 1/2" (R13) 5100 PSI 35 MPa 350BAR Flame Resistant MSHA 2G-1C-14C/45

X-Life™ XCP5S

Product Numbers

SAP	Product #	ID	ID		OD		Max Working Pressure		Bend Radius		MIN BURST Pressure		Fitting Type	Weight (lb/ft)
		Fraction	in.	mm.	in.	mm.	PSI	MPa	in.	mm.	PSI	Mpa		
20882963	XCP5S-06	3/8	0.38	10.00	0.84	21.40	5100	35	3.50	90.00	20400	140.00	SG	0.48
20879434	XCP5S-08	1/2	0.50	12.50	0.97	24.60	5100	35	3.50	90.00	20400	140.00	SG	0.58
20882965	XCP5S-10	5/8	0.63	16.00	1.11	28.20	5100	35	4.70	120.00	20400	140.00	SG	0.79
20864025	XCP5S-12	3/4	0.75	19.00	1.27	32.20	5100	35	4.70	120.00	20400	140.00	SG	0.98
20867348	XCP5S-16	1	1.00	25.00	1.52	38.70	5100	35	5.90	150.00	20400	140.00	SG	1.42
20879437	XCP5S-20	1-1/4	1.25	31.50	1.79	45.50	5100	35	10.70	270.00	20400	140.00	SG	1.71
20864029	XCP5S-24	1 1/2	1.50	38.00	2.28	57.80	5100	35	19.60	500.00	20400	140.00	S6, SE	3.35
20867503	XCP5S-32	2	2.00	51.00	2.80	71.10	5100	35	24.80	630.00	20400	140.00	S6, SE	4.76