



X-Life™ XNR7

XNR7 is a medium-pressure thermoplastic hose with a non-perforated cover. This hose is compatible with petroleum-, water- and synthetic-based fluids for mobile equipment, lube lines, blowout preventers, hydraulic lifts and construction machinery requiring SAE 100R7 non-conductivity standards.

Performance + Specs

◊ SAE 100R7

Inner Tube

Polyester White

Reinforcement

1 or 2 Layers, Braided Synthetic Fibers

Cover

Polyurethane, Non Pin-Pricked Orange

Temperature Range

-40°F / -40°C ~ 212°F / 100°C

Key Features

4:1 Safety Factor

Non-Conductive

Branding

CONTINENTAL X-LIFE™ XNR7-04 1/4 (DN6) SAE 100R7 NONCONDUCTIVE 3000 PSI (21.0 MPA) MSHA IC-305

X-Life™ XNR7

Product Numbers														
SAP	Product #	ID	ID	OD		Max Working Pressure		Bend Radius		MIN BURST Pressure		Fitting Type	Weight (lb/ft)	
		Fraction	in.	mm.	in.	mm.	PSI	MPa	in.	mm.	PSI	Mpa		
21151340	XNR7-03	3/16	0.18	4.76	0.38	9.60	3046	21.00	0.98	25.00	12184	81.01	UCT	0.16
21151341	XNR7-04	1/4	0.25	6.50	0.48	12.20	3046	21.00	1.38	35.00	12184	84.01	UC	0.17
21151342	XNR7-05	5/16	0.32	8.10	0.56	14.30	2756	19.00	1.77	45.00	11024	76.01	UC	0.18
21151343	XNR7-06	3/8	0.38	9.70	0.63	16.00	2321	16.00	2.17	55.00	9284	64.01	UC	0.19
21151344	XNR7-08	1/2	0.51	13.00	0.80	20.30	2031	14.00	2.95	75.00	8124	56.01	UC	0.2
21151345	XNR7-12	3/4	0.77	19.50	1.07	27.10	1305	9.00	5.51	140.00	5220	35.99	UC	0.21
21151346	XNR7-16	1	1.00	25.40	1.34	34.00	1015	7.00	7.48	190.00	4060	27.99	UC	0.22

No Fittings Found