

Continental **X-LIFE™** XR7

X-Life™ XR7

XR7 is a medium-pressure, thermoplastic hose with a perforated cover. It is compatible with petroleum-, water- and synthetic-based fluids for mobile equipment, lube lines, blowout preventers, hydraulic lifts and construction machinery.

Performance + Specs

◦ SAE 100R7

Inner Tube

Polyester White

Reinforcement

1 or 2 Layers, Braided Synthetic Fibers

Cover

Polyurethane, Pin-Pricked Black

Temperature Range

-40°F / -40°C ~ 212°F / 100°C

Key Features

1/2 Bend Radius

4:1 Safety Factor

Branding

CONTINENTAL X-LIFE™ XR7-03 3/16 (DN5) SAE 100R7 NON-CONDUCTIVE 3000 PSI (21.0 MPA) MSHA IC-305

X-Life™ XR7

Product Numbers

SAP	Product #	ID	ID	OD	Max Working Pressure		Bend Radius		MIN BURST Pressure		Fitting Type	Weight (lb/ft)		
		Fraction	in.	mm.	in.	mm.	PSI	MPa	in.	mm.	PSI	Mpa		
21151332	XR7-02	1/8	0.13	3.30	0.33	8.30	3046	21.00	0.98	25.00	12184	84.01	UCT	0.15
21151333	XR7-03	3/16	0.19	4.80	0.38	9.60	3046	21.00	0.98	25.00	12184	84.01	UCT	0.16
21151334	XR7-04	1/4	0.25	6.35	0.48	12.20	3046	21.00	1.38	35.00	12184	84.01	UC	0.17
21151335	XR7-05	5/16	0.31	7.90	0.56	14.30	2756	19.00	1.77	45.00	11024	76.01	UC	0.18
21151336	XR7-06	3/8	0.38	9.50	0.63	16.00	2321	16.00	2.17	55.00	9284	64.01	UC	0.19
21151337	XR7-08	1/2	0.50	12.70	0.80	20.30	2031	14.00	2.95	75.00	8124	56.01	UC	0.2
21151338	XR7-12	3/4	0.75	19.00	1.07	27.10	1305	9.00	5.51	140.00	5220	35.99	UC	0.21
21151339	XR7-16	1	1.00	25.40	1.34	34.00	1015	7.00	7.48	190.00	4060	27.99	UC	0.22

No Fittings Found