



X-Life™ XR8

XR8 is a high-pressure thermoplastic hose with a perforated cover for petroleum-, water- and synthetic-based fluids for mobile equipment, lube lines, blowout preventers, hydraulic lifts and construction machinery.

Performance + Specs

◦ SAE 100R8

Inner Tube

Polyester White

Reinforcement

1 or 2 Layers, Braided Aramid Fibers

Cover

Polyurethane, Pin-Pricked Black

Temperature Range

-40°F / -40°C ~ 212°F / 100°C

Key Features

4:1 Safety Factor

Branding

CONTINENTAL X LIFE™ XR8-08 1/2 (DN12) SAE 100R8 3500 PSI (24.5 MPA) MSHA IC-305

X-Life™ XR8

Product Numbers

SAP	Product #	ID	ID	OD	Max Working Pressure		Bend Radius		MIN BURST Pressure		Fitting Type	Weight (lb/ft)		
		Fraction	in.	mm.	in.	mm.	PSI	MPa	in.	mm.	PSI	Mpa		
21151353	XR8-03	3/16	0.19	4.80	0.35	8.90	5076	35.00	1.18	30.00	20304	139.99	UCT	0.16
21151354	XR8-04	1/4	0.25	6.35	0.45	11.50	5076	35.00	1.97	50.00	20304	139.99	UC	0.17
21131355	XR8-06	3/8	0.38	7.90	0.61	15.50	4061	28.00	2.36	60.00	16244	111.99	UC	0.19
21151356	XR8-08	1/2	0.50	12.70	0.78	19.90	3553	24.50	3.15	80.00	14212	97.98	UC	0.2

No Fittings Found