



X-Life™ XTR7

XTR7 is a medium-pressure, twin-line thermoplastic hose with a perforated cover. It is compatible with petroleum-, water- and synthetic-based fluids for mobile equipment, lube lines, blowout preventers, hydraulic lifts and construction machinery.

Performance + Specs

- SAE 100R7

Inner Tube

Polyester White

Reinforcement

1 or 2 Layers, Braided Synthetic Fibers

Cover

Polyurethane, Pin-Pricked Black

Temperature Range

-40°F / -40°C ~ 212°F / 100°C

Key Features

- 4:1 Safety Factor
- Twin-Line Hose

Branding

X-Life™ XTR7

Product Numbers

SAP	Product #	ID	ID		OD		Max Working Pressure		Bend Radius		MIN BURST Pressure		Fitting Type	Weight (lb/ft)
		Fraction	in.	mm.	in.	mm.	PSI	MPa	in.	mm.	PSI	Mpa		
21151347	XTR7-04	1/4	.25	6.35	0.48	12.20	3046	21.00	1.38	35.00	12184	84.01	UC	0.17
21151348	XTR7-06	3/8	.38	7.90	0.63	16.00	2321	16.00	2.17	55.00	9284	64.01	UC	0.19
21151349	XTR7-08	1/2	.50	12.70	0.80	20.30	2031	14.00	2.95	75.00	8124	56.01	UC	0.2

No Fittings Found