



BLACK FLEXTRA II

Used by tank trucks, bulk petroleum stations, and others to transfer ethanol blends and petroleum products under pressure, suction and/or gravity flow. Extremely flexible and lightweight to provide excellent service. Not recommended where aromatic content exceeds 50%.

Performance + Specs

Tube

- Nitrile (NBR)

Cover

- Nitrile / PVC Blend

Reinforcement

- Spiral-Plied Synthetic Fabric
- Double Wire Helix

Temperature Range

- 40°F / -40°C ~ 180°F / 82°C

Design Factor

- 4:1

Packaging

- 100ft lengths, coiled and polywrapped

Coupling

- Refer to the Continental Industrial Hose Assembly Manual for crimp specifications.

Branding

CONTINENTAL BLACK FLEXTRA II 150 PSI WP MADE IN CANADA

Black Flextra II

Order Codes: 543-142

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/2	38.10	1.99	50.44	100	Black	3.00	76.20	29.00	736.60	150	1.03	0.93	1.38	20017616
2	50.80	2.48	63.09	100	Black	4.00	101.60	29.00	736.60	150	1.03	1.17	1.74	20017617
				400	Black	4.00	101.60	29.00	736.60	150	1.03	1.17	1.74	20017618
2-1/2	63.50	3.04	77.15	100	Black	6.00	152.40	29.00	736.60	150	1.03	1.63	2.42	20017619
3	76.20	3.54	89.84	100	Black	7.50	190.50	29.00	736.60	150	1.03	1.92	2.85	20017620
4	101.60	4.57	116.02	100	Black	10.00	254.00	29.00	736.60	150	1.03	2.74	4.08	20017621