



BLAST

Heavy-duty hose for steel shot or sand blasting in cleaning or finishing metal, stone, glass or other surfaces. 549-805 Conti-Clean Survivor Tube (549-805 2 Ply, 549-776 4 Ply), Chemituf (549-020 2 Ply & 549-027 4 Ply). As opposed to most hose products, Blast hose couplings are inserted over the hose cover instead of inside the hose itself. The OD is therefore what matters the most. All blast hoses have critical OD tolerances. Available in 2 Ply and 4 Ply.

Performance + Specs

Tube - ContiClean Survivor® 2 Ply (549-805) - ContiClean Survivor® 4 Ply (549-776) - Chemituf 2 PLY (549-220) - Chemituf 4 Ply (549-027) - Static Dissipating / Static Conductive	Cover SBR synthetic rubber (wrapped impression)
Reinforcement Spiral-plyed synthetic fabric	Temperature Range -25°F / -32°C ~ 180°F / 82°C
Design Factor 4:1	Packaging 50ft lengths, Coiled & Poly-Wrapped
Coupling Contact fitting manufacturer for proper fitting recommendation and coupling procedure.	Non Stock / Sizes For special production run minimum requirements, Contact Customer Service.

Branding

CONTINENTAL BLAST 150 MAX WP MADE IN CANADA

Blast

Order Codes: 549-027 (Chemituf 4 Ply), 549-020 (Chemituf 2 Ply), 549-805 (Conticlean Survivor Tube 2 Ply), 549-776 (Conticlean Survivor 4 Ply)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/8	9.53	0.71	18.13	50	Black	600	4.14			150	1.03	0.15	0.23	20106004
1/2	12.70	1.13	28.70	50	Green	600	4.14			150	1.03	0.44	0.66	20019028
				50	Black	600	4.14			150	1.03	0.42	0.63	20018946
1/2	12.70	1.13	28.66	50	Black	600	4.14			150	1.03	0.41	0.60	20673581
				100	Black	600	4.14			150	1.03	0.42	0.63	20018947
3/4	19.05	1.49	37.85	50	Green	600	4.14			150	1.03	0.72	1.06	20019030
				100	Green	600	4.14			150	1.03	0.72	1.06	20019031
3/4	19.05	1.47	37.25	50	Black	600	4.14			150	1.03	0.64	0.96	20018953
				100	Black	600	4.14			150	1.03	0.64	0.96	20018954
3/4	19.05	1.51	38.25	50	Black	600	4.14			150	1.03	0.67	1.00	21127644
1	25.40	1.88	47.72	50	Green	600	4.14			150	1.03	1.09	1.62	20019032
				100	Green	600	4.14			150	1.03	1.09	1.62	20019033
				50	Black	600	4.14			150	1.03	1.07	1.60	20018962
1	25.40	1.88	47.80	50	Black	600	4.14			150	1.03	1.04	1.55	20673583
				100	Black	600	4.14			150	1.03	1.07	1.60	20018963
1-1/4	31.75	2.13	54.15	50	Black	600	4.14			150	1.03	1.26	1.87	20018970
				100	Black	600	4.14			150	1.03	1.26	1.87	20018972
				50	Black	600	4.14			150	1.03	1.25	1.86	20673584
				50	Green	600	4.14			150	1.03	1.32	1.97	20019035
1-1/4	31.75	2.15	54.55	100	Black	600	4.14	29.00	736.60	150	1.03	1.26	1.87	21130942
				100	Black	600	4.14			150	1.03	1.25	1.86	21161412
				100	Green	600	4.14			150	1.03	1.32	1.97	20019037
1-1/2	38.10	2.38	60.42	50	Green	600	4.14			150	1.03	1.46	2.17	20019038
				100	Green	600	4.14			150	1.03	1.46	2.17	20019040
1-1/2	38.10	2.37	60.10	50	Black	600	4.14			150	1.03	1.40	2.08	20018980
				100	Black	600	4.14			150	1.03	1.40	2.08	20018982
1-1/2	38.10	2.38	60.50	50	Black	600	4.14			150	1.03	1.36	2.03	20673585
				50	Black	600	4.14			150	1.03	1.71	2.55	20677610
2	50.80	2.88	73.20	100	Black	600	4.14			150	1.03	1.78	2.65	20018993
				400	Black	600	4.14			150	1.03	1.78	2.65	20018991
2	50.80	2.85	72.32	50	Black					150	1.03	1.65	2.46	21135985
				50	Green	600	4.14			150	1.03	1.74	2.59	20019042
3	76.20	3.99	101.35	50	Black					150	1.03	2.88	4.28	21124656