



CLEARWATER SOFTWALL

Clearwater is an NSF/ANSI/CAN-61 certified drinking water hose designed for safe handling of drinking water and demineralized water in domestic and industrial applications. It is available in both softwall discharge (542-872 CLEARWATER SOFTWALL) and suction/discharge (542-868 CLEARWATER FLEXTRA) configurations, with an optional crush-resistant suction/discharge version (542-870 CLEARWATER FLEXTRA CCR) for demanding environments.

Performance + Specs

Tube - Transparent, absolutely neutral to taste and odor, PE material. - Compliant to FDA and USDA	Cover Blue EPDM with wrapped impression. Ozone, weather UV resistant.
Reinforcement Synthetic Spiral Plied Fabric	Temperature Range -40°F / -40°C ~ 212°F / 100°C
Design Factor 4:1	Packaging Coiled & Poly-Wrapped
Coupling - Contact fitting manufacturer for proper fitting recommendation and coupling procedure NSF C0454763 - 061.pdf	Downloads

Branding

CONTINENTAL CLEARWATER SOFTWALL POTABLE WATER 150 PSI WP CERTIFIED TO NSF/ANSI/CAN 61-G. MEETS FDA. MADE IN CANADA.

Clearwater Softwall

Order Codes: 542-872 (Softwall)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.34	34.16	100	Blue	600	4.14	150	1.03	0.38	0.56	21053710
1-1/4	31.75	1.59	40.51	100	Blue	600	4.14	150	1.03	0.45	0.67	21053711
1-1/2	38.10	1.84	46.86	100	Blue	600	4.14	150	1.03	0.53	0.79	21053712
2	50.80	2.36	60.00	100	Blue	600	4.14	150	1.03	0.73	1.08	21053713
2-1/2	63.50	2.86	72.70	100	Blue	600	4.14	150	1.03	0.89	1.33	21053714
3	76.20	3.39	86.04	100	Blue	600	4.14	150	1.03	1.14	1.70	21053715
4	101.60	4.39	111.44	100	Blue	600	4.14	150	1.03	1.50	2.23	21053716