



DAMPF TRIX 6000

The high-temperature resistant Continental DAMPF TRIX ® 6000 steam hose has been designed to meet the most severe working conditions for conveying saturated steam in the chemical and petrochemical industry, in refineries, the building industry, in shipyards and for various other industrial applications. It is made of an extremely heat resistant EPDM lining and cover assuring the transport of pure, saturated steam at +210°C and 18 bar, or even at +220°C and 23 bar for short-time service. DAMPF TRIX ® 6000 is manufactured to European standards.

Performance + Specs

Tube

- EPDM Rubber (Conductive)

Cover

- EPDM Rubber (Conductive)
- Resistant to ozone, weather, UV and abrasion.

Reinforcement

- Dual steel wire braids
- Excellent Resistance to Corrosion

Temperature Range

- -40°F / -40°C ~ 410°F / 210°C

Design Factor

- 20:1

Packaging

- Coiled & Poly-Wrapped

Branding

Continental DAMPF TRIX® 6000 261 psi (18 bar) Made in Germany

Dampf Trix 6000

Order Codes: 505-134

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.05	1.30	33.02	131	Black / Red	2611	18.00	7.48	189.99	261	1.8	0.60	0.90	20836409
1-1/2	38.10	2.13	54.10	131	Black / Red	2611	18.00	14.94	379.48	261	1.8	1.21	1.80	20836412