

DATA GUARD HB

DataGuard is engineered to deliver a constant supply of coolant to server manifolds. It withstands extreme temperatures and features a peroxide-cured EPDM tube that maximizes heat resistance and coolant purity. The cover meets UL 94 HB flame safety standard.

Performance + Specs

Tube

- EPDM, peroxide cured

Cover

- EPDM, UL 94 HB flame resistant

Reinforcement

- One layer, braided synthetic textile

Temperature Range

- -40°F / -40°C ~ 210°F / 99°C

Design Factor

- 4:1

Packaging

Reels (1")
Bulk boxes (1-1/2" - 2")

Coupling

- contact fitting manufacturer for proper fitting recommendation & coupling procedure.

Branding

Continental DataGuard 2" 200 PSI (1.38 MPa) UL 94 HB Made in USA

DataGuard HB

Order Codes: 536-055

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Min. Burst (PSI)	Min. Burst (Mpa)	Color	Bend Radius		WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
							(in.)	(mm)					
1	25.40	1.47	37.34	800	5.52	Black	5.00	127.00	200	1.38	0.52	0.77	21204605
1-1/2	38.10	2.08	52.83	800	5.52	Black	8.00	203.20	200	1.38	0.95	1.41	21204627
2	50.80	2.52	64.01	800	5.52	Black	12.00	304.80	200	1.38	1.06	1.58	21204635