



DEADMAN SANDBLAST

Continental Deadman Sandblast hose is for use with systems for the automatic shut-off of sandblasting equipment at the operator end of the system. Used in a pneumatic closed circuit pattern, deadman hose is connected to air-actuated shut valves which, in turn, are controlled at all times by the sandblast operator via a “deadman” switch at the nozzle end of the sandblast hose.

Performance + Specs

Tube

- EPDM Rubber

Cover

- EPDM Rubber

Reinforcement

- Spiral Synthetic Yarn

Temperature Range

- -20°F / -29°C ~ 190°F / 88°C

Design Factor

- 4:1

Packaging

- 450ft–750ft Reels
- Maximum 2 pieces, minimum length 25ft

Branding

3/16" ID (4.8 mm) Sandblast Deadman Made in USA Continental

Deadman Sandblast

Order Codes: 569-698 (Yellow / Green), 569-676 (Red / Black), 569-595 (Yellow / Yellow)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1/4	5.00	0.44	11.10	500	Yellow / Green	800	5.52	200	1.38	0.16	0.24	20805226
3/16	5.00	0.44	11.10	500	Red / Black	800	5.52	200	1.38	0.15	0.22	20709610
				500	Yellow / Yellow	800	5.52	200	1.38	0.16	0.24	20027303