



## DIESEL OIL SOFTWALL

Diesel Oil SW is designed for offshore oil rig applications, specifically for transferring petroleum-based products with up to 50% aromatic content. Its specialized tube and cover compounds provide maximum oil resistance, ensuring durability and performance in demanding environments.

### Performance + Specs

#### Tube

- NITRILE (NBR) (Mx 50% aromatic content, RMA Class A High Oil Resistant)

#### Cover

- CHLOROPRENE (CR) (MSHA Fire Resistant) Wrapped impression

#### Reinforcement

- Spiral-Plied Synthetic Fabric With Antistatic Wire

#### Temperature Range

- -35°F / -37°C ~ 200°F / 93°C

#### Design Factor

- 4:1

#### Packaging

- Coiled and poly-wrapped

#### Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

### Branding

CONTINENTAL DIESEL OIL MADE IN CANADA

#### Diesel Oil Softwall

**Order Codes:** 543-272 (3"-6")

### Product Numbers

| ID (in) | ID (mm) | Nom. OD (in.) | Nom. OD (mm) | Length (ft) | Color | Vacuum (in.) | Vacuum (mm) | WP (PSI) | WP (MPa) | Weight (lbs/ft) | Weight (kg/m) | Part Number     |
|---------|---------|---------------|--------------|-------------|-------|--------------|-------------|----------|----------|-----------------|---------------|-----------------|
| 4       | 101.60  | 4.54          | 115.20       | 400         | Black | 29.00        | 736.60      | 150      | 1.03     | 2.16            | 3.21          | <b>20195077</b> |
| 6       | 152.40  | 6.59          | 167.28       | 400         | Black | 29.00        | 736.60      | 150      | 1.03     | 3.50            | 5.21          | <b>20195076</b> |