



DRY CEMENT HARDWALL

Heavy duty high performance suction and discharge hose for the bulk transfer of dry cement and barites from supply vessels to off-shore platforms and drilling rigs

Performance + Specs

Tube

- Chemituf (Static Dissipating)

Cover

- SBR (Wrapped Finish)

Reinforcement

- Spiral-Plied fabric
- Double Helix Wire

Temperature Range

- -25°F / -32°C ~ 180°F / 82°C

Design Factor

- 4:1

Packaging

- Coiled & Poly-Wrapped

Branding

CONTINENTAL DRY CEMENT HARDWALL ##### MADE IN CANADA / CONTINENTAL CONTITECH BARITES ##### MADE IN CANADA

Dry Cement Hardwall

Order Codes: 549-275 (150 PSI Working Pressure)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
5	127.00	5.85	148.54	400	Black	30.00	762.00	29.00	736.60	150	1.03	4.79	7.13	20703501