

ELITE HOT WATER

Designed for use on molding machines & presses where the hose application should withstand high temperature fluid & minimize the volumetric expansion during pressure spikes. The tube compound can handle up to 300F coolant temperatures intermittently. Exceeds SAE J20R3 class D3-HT-EC test standard.

Performance + Specs

Tube

- Black EPDM (Meets SAE 20R 3 D-3 HT EC requirements)

Cover

- Blue or red EPDM (Meets SAE 20R 3 D-3 HT EC requirements)

Reinforcement

- Spiral Aramid Yarn

Temperature Range

- -40°F / -40°C ~ 300°F / 149°C

Design Factor

- 4:1

Packaging

- 500' coiled reels (max 3 per reel)

Coupling

- Contact fitting manufacturer for proper fitting recommendation & coupling procedure.

Branding

Continental ContiTech Elite Hot Water 150 PSI (10.3 Bar) SAE J20R3-D3-HT-EC Made in USA

Elite Hot Water

Order Codes: 569-190 (Blue), 569-191 (Red)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
13/32	10.00	0.71	18.00	500	Blue	150	1.03	0.15	0.23	20943781
				500	Red	150	1.03	0.15	0.23	20960336
1/2	13.00	0.83	21.00	500	Blue	150	1.03	0.19	0.28	20943785
				500	Red	150	1.03	0.19	0.28	20960337