

EPDM ACID

EPDM hose is engineered to handle a wide range of chemicals, acids, and alcohols with ease, in both suction and discharge service. Whether you're working in industrial, processing, or transport environments.

Performance + Specs

Tube EPDM	Cover EPDM (Corrugated)
Reinforcement - Spiral-Plied Synthetic Fabric - Double Wire Helix	Temperature Range -40°F / -40°C ~ 221°F / 105°C
Design Factor 4:1	Packaging Wrapped, Coiled and Palletized
Coupling Contact fitting manufacturer for proper fitting recommendation and coupling procedures.	

Branding

CONTINENTAL ACID & CHEMICAL HOSE 150 PSI WP MADE IN CANADA

EPDM Acid

Order Codes: 546-211 (1-1/2"-6")

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/2	38.10	1.94	49.16	100	Yellow	600	4.14	2.30	58.42	29.00	736.60	150	1.03	0.76	1.13	20917684
2	50.80	2.44	61.86	100	Yellow	600	4.14	3.00	76.20	29.00	736.60	150	1.03	0.98	1.45	20913795
3	76.20	3.55	90.19	100	Yellow	600	4.14	4.50	114.30	29.00	736.60	150	1.03	1.83	2.72	21091949
				100	Yellow	600	4.14	4.50	114.30	29.00	736.60	150	1.03	1.83	2.72	20917685
4	101.60	4.57	115.98	100	Yellow	600	4.14	6.00	152.40	29.00	736.60	150	1.03	2.50	3.72	20917686
6	152.40	6.65	168.99	100	Yellow	600	4.14	9.00	228.60	29.00	736.60	150	1.03	4.64	6.91	20917687