



EXSTATIC

The Continental Exstatic® is purpose-built for the transfer of dry, bulk foodstuffs—ideal for tank truck and in-plant service where static electricity is a concern. Featuring a static-dissipating UHMWPE tube and a rugged blue corrugated SBR cover, this hose meets FDA and USDA standards for food safety. Exstatic® ensures safe, efficient, and compliant handling of powders like flour, sugar, and grains in high-volume operations and abrasives.

Performance + Specs

Tube UHMWPE (FDA/USDA compliant) - Static Dissipating/Static Conductive	Cover - SBR Synthetic Rubber (Corrugated) - Spiral Transfer Brand (Wrapped Impression)
Reinforcement Spiral-plied Synthetic Fabric with Double Wire Hel	Temperature Range -25°F / -32°C ~ 180°F / 82°C
Design Factor 4:1	Packaging 100ft length, coiled, polywrapped
Coupling Refer to the Continental Industrial Hose Assembly Manual for crimp specifications	Non Stock / Sizes For special production run minimum requirements, see Appendix D

Downloads

- [Food Hose Cleaning Guide](#)

Branding

Continental Exstatic Dry Material Handling Meets FDA 150 PSI Made in Canada

Exstatic

Order Codes: 549-608

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
2	50.80	2.47	62.73	100	Blue	600	4.14	8.00	203.20	29.00	736.60	150	1.03	1.08	1.60	20019899
4	101.60	4.55	115.58	100	Blue	600	4.14	16.00	406.40	29.00	736.60	150	1.03	2.55	3.79	20019904
5	127.00	5.62	142.71	100	Blue	600	4.14	20.00	508.00	29.00	736.60	150	1.03	3.75	5.58	20019905