



EXTREMEFLEX® DATAGUARD

EXTREMEFLEX DATAGUARD is an ultra-flexible and lightweight source feed hose, engineered to deliver a constant supply of coolant throughout your data center. Its advanced design allows for an impressive 1:1 bend radius, ensuring easy routing and installation within rack systems. Our cover is certified to UL 94 HB flame safety standards which provides peace of mind in your high-heat environments. Meanwhile, the peroxide-cured tube minimizes leaching protecting the integrity of both your coolant and equipment. 549-356 (White Layline), 549-689 (Red Layline), 549-578 (Blue Layline).

Performance + Specs

Tube Black EPDM (Peroxide Cure)	Cover Corrugated Black EPDM (abrasion resistant, UL 94 HB Flame Resistant) (wrapped impression)
Reinforcement Spiral-plyed fabrics with double helix wire	Temperature Range -40°F / -40°C ~ 200°F / 93°C
Design Factor 4:1	Packaging Coiled & Poly-Wrapped
Coupling Contact fitting manufacturer for proper fitting recommendation and coupling procedures.	

Branding

CONTINENTAL EXTREMEFLEX DATAGUARD 150PSI WP 150PSI WP EPDM-P UL 94 HB MADE IN CANADA

ExtremeFlex® DataGuard

Order Codes: 549-356 (HB - White Layline), 549-578 (HB - Blue Layline)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.10	1.15	29.30	100	Black	600	4.14	0.75	19.00	29.00	736.60	150	1.03	0.34	0.51	21203745
				200	Black	600	4.14	0.75	19.00	29.00	736.60	150	1.03	0.34	0.51	21203747
1	25.40	1.40	35.60	100	Black	600	4.14	1.00	25.40	29.00	736.60	150	1.03	0.43	0.64	21203748
				200	Black	600	4.14	1.00	25.40	29.00	736.60	150	1.03	0.43	0.64	21203749
				400	Black	600	4.14	1.00	25.40	29.00	736.60	150	1.03	0.43	0.64	21217773
1-1/4	31.80	1.66	42.10	100	Black	600	4.14	1.25	31.75	29.00	736.60	150	1.03	0.54	0.80	21203750
				200	Black	600	4.14	1.25	31.75	29.00	736.60	150	1.03	0.54	0.80	21203751
				400	Black	600	4.14	1.25	31.75	29.00	736.60	150	1.03	0.54	0.80	21217774
1-1/2	38.10	1.91	48.40		Black	600	4.14	1.50	38.00	29.00	736.60	150	1.03	0.62	0.93	21217777
				100	Black	600	4.14	1.50	38.00	29.00	736.60	150	1.03	0.62	0.93	21203752
				200	Black	600	4.14	1.50	38.00	29.00	736.60	150	1.03	0.62	0.93	21203753
2	50.80	2.44	62.10	100	Black	600	4.14	2.00	50.80	29.00	736.60	150	1.03	0.86	1.27	21203754
				200	Black	600	4.14	2.00	50.80	29.00	736.60	150	1.03	0.86	1.27	21203755
				400	Black	600	4.14	2.00	50.80	29.00	736.60	150	1.03	0.86	1.27	21217778
2	50.80	2.44	61.98	100	Black	600	4.14	2.00	50.80	29.00	736.60	150	1.03	0.86	1.27	21215933
2-1/2	63.50	3.01	76.50	100	Black	600	4.14	2.52	64.01	29.00	736.60	150	1.03	1.25	1.87	21203756
				200	Black	600	4.14	2.52	64.01	29.00	736.60	150	1.03	1.25	1.87	21203757
				400	Black	600	4.14	2.52	64.01	29.00	736.60	150	1.03	1.25	1.87	21217969
3	76.20	3.51	89.20	100	Black	600	4.14	3.00	76.20	29.00	736.60	150	1.03	1.49	2.22	21203758
				200	Black	600	4.14	3.00	76.20	29.00	736.60	150	1.03	1.49	2.22	21203759
				400	Black	600	4.14	3.00	76.20	29.00	736.60	150	1.03	1.49	2.22	21217926
4	101.60	4.53	115.06	100	Black	600	4.14	4.00	101.60	29.00	736.60	150	1.03	2.12	3.15	21203760
				200	Black	600	4.14	4.00	101.60	29.00	736.60	150	1.03	2.12	3.15	21203761
1	-	1.40	35.56	100	Black	600	4.14	1.00	25.40	29.00	736.60	150	1.03	0.43	0.64	21217083