



## EXTREMEFLEX POTABLE WATER

Engineered with ExtremeFlex™ technology, this hose delivers exceptional flexibility and ease of handling. Designed for potable water suction and discharge, it is suitable for use with Potable Water – Meets FDA requirements and complies with 3-A Standard 18-03 and FDA 21 CFR 177.2600. Ideal for applications requiring a highly flexible, lightweight, and durable hose for safe, sanitary potable water handling.

### Performance + Specs

#### Tube

- Natural Rubber (NR) - Meets 3-A 18-03 \*FDA 21 CFR 177.2600

#### Cover

- EPDM Rubber

#### Reinforcement

- Spiral Plied synthetic fabric with dual helix wire

#### Temperature Range

- 40°F / -40°C ~ 180°F / 82°C

#### Design Factor

- 3:1

#### Packaging

- Coiled & Poly-Wrapped

#### Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

#### Non Stock / Sizes

- 100 ft. subject to minimum run

### Branding

CONTINENTAL EXTREMEFLEX WATER TRANSFER Meets FDA,150 PSI WP MADE IN CANADA

#### ExtremeFlex Potable Water

Order Codes: 542-235

### Product Numbers

| ID (in) | ID (mm) | Nom. OD (in.) | Nom. OD (mm) | Length (ft) | Color  | Bend Radius (in.) | Bend Radius (mm) | Vacuum (in.) | Vacuum (mm) | WP (PSI) | WP (MPa) | Weight (lbs/ft) | Weight (kg/m) | Part Number |
|---------|---------|---------------|--------------|-------------|--------|-------------------|------------------|--------------|-------------|----------|----------|-----------------|---------------|-------------|
| 2       | 50.80   | 2.44          | 62.06        | 100         | Orange | 2.00              | 50.80            | 29.00        | 736.60      | 150      | 1.03     | 1.00            | 1.49          | 20569587    |
| 3       | 76.20   | 3.55          | 90.18        | 100         | Orange | 3.00              | 76.20            | 29.00        | 736.60      | 150      | 1.03     | 1.87            | 2.78          | 20569588    |