

FIRE ENGINE BOOSTER

Continental Fire Engine Booster is for use in high-pressure fire engine booster services. It also has many applications in other heavy-duty industrial and municipal operations.

Performance + Specs

Tube Synthetic Rubber	Cover Synthetic Rubber
Reinforcement 2 Braid Synthetic Yarn	Temperature Range 0°F / -18°C ~ 180°F / 82°C
Design Factor 4:1	Packaging Cartons: 1000ft (50ft increments) Cut lengths: 50ft (2 pieces); 100ft (1 piece) Coupled lengths: 50ft (2 pieces); 100ft (1 piece)
Coupling Coupled Assemblies Available	Non Stock / Sizes For special production run minimum requirements, Contact Customer Service.

Branding

Continental 1" Fire Engine Booster. Made in USA

Fire Engine Booster

Order Codes: 536-382

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.10	1.25	31.75	50	Red	2400	16.55	800	5.52	0.49	0.73	20023040
				100	Red	2400	16.55	800	5.52	0.49	0.73	20023041
				150	Red	2400	16.55	800	5.52	0.47	0.69	20023042
				200	Red	2400	16.55	800	5.52	0.46	0.68	20023043
1	25.40	1.53	38.86	50	Red	2400	16.55	800	5.52	0.63	0.94	20023049
				100	Red	2400	16.55	800	5.52	0.63	0.94	20023050
				150	Red	2400	16.55	800	5.52	0.66	0.99	20023052
				200	Red	2400	16.55	800	5.52	0.64	0.95	20023053