

FIRE EXT. & BOOSTER HOSE EX 589 3/4"  2095 250 PSI W.P.

FIRE EXTINGUISHER UL92

Designed for fire extinguisher and booster hose for use on portable, wheeled, and stationary fire extinguishers, and also as booster hose on fire apparatus. Also for use on fire extinguishers requiring characteristics for low-temperature flexibility at minus 54°C (minus 65°F). Exceeds UL-92 Standard for Fire Extinguisher and Booster Hose

Performance + Specs

Tube

- EPDM Rubber

Cover

- EPDM Rubber

Reinforcement

- Spiral Synthetic Yarn

Temperature Range

- -65°F / -54°C ~ 200°F / 93°C

Design Factor

- 4:1

Packaging

- Bulk or Specific Cut to Length

Branding

EX 589 3/4" UL LISTED FIRE EXT. & BOOSTER HOSE 250 PSI WORKING PRESSURE - TESTED TO 500 LB. FOR USE AT -54C (-65F)

Fire Extinguisher UL92

Order Codes: 569-022 (Black)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.10	1.26	32.10	50	Black	250	1.72	0.41	0.61	20026153
1	25.10	1.52	38.70	50	Black	250	1.72	26.95	40.11	20130576