



FIRE S&D

Water suction

Performance + Specs

Tube SBR	Cover SBR (Wrapped Finish)
Reinforcement - Spiral-Plied Fabrics - Double Steel Helix Wire	Temperature Range -25°F / -32°C ~ 180°F / 82°C
Design Factor 4:1	Packaging Coiled & Poly-Wrapped
Coupling Contact fitting manufacturer for proper fitting recommendation and coupling procedure.	

Branding

CONTINENTAL MADE IN CANADA (3/4" transfer branding)

Fire S&D
Order Codes: 542-070

Product Numbers														
ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.58	40.10	50	Black	3.00	76.20	29.00	736.60	400	2.76	0.75	1.11	20811655
1-1/2	38.10	2.08	52.80	50	Black	4.50	114.30	29.00	736.60	400	2.76	1.06	1.58	20811656
2	50.80	2.61	66.41	50	Black	6.00	152.40	29.00	736.60	300	2.07	1.46	2.17	20811657
3	76.20	3.65	92.59	100	Black	12.00	304.80	29.00	736.60	300	2.07	2.28	3.40	20811659