



FLEXCOOL JUMPER V-0

FlexCool Jumper V-0 transitions cooling fluid from the manifold to individual server blades, offering compatibility with crimped, clamped, and push-on attachment methods. Its peroxide-cured EPDM tube maximizes heat resistance and coolant purity. The cover meets UL 94 V-0 flame safety standard.

Performance + Specs

Tube EPDM (peroxide cure)	Cover CPE Rubber (UL 94 V-0 flame resistant)
Reinforcement 1 layer, braided synthetic textile	Temperature Range -40°F / -40°C ~ 190°F / 88°C
Design Factor 4:1	Packaging 500ft reels
Coupling Contact fitting manufacturer for proper coupling procedure.	

Branding

Continental FlexCool Jumper 150 PSI (1.0 Mpa) EPDM-P UL 94 V-0 Made in USA

FlexCool Jumper V-0

Order Codes: 535-358

Product Numbers													
ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius		WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number	
						Color	(in.) (mm)						
1/2	12.70	0.82	20.83	600	4.14	Black	3.00	76.20	150	1.03	0.20	0.31	21213948
1	25.40	1.34	34.00	600	4.14	Black	6.00	152.40	150	1.03	0.36	0.54	21212477