

FLEXDOCK VERSAFUEL

Transfer of crude, diesel, biodiesel blend, B-100, ethanol blend, gasoline, oil and petroleum product up to 60% aromatic content between docks and ships. All hose tested to ARPM IP-8 and Coast Guard Federal Regulations, title 33,Chapter 1, Subpart C clause 154.500.

Performance + Specs

Tube

- Nitrile (NBR) - Static Disapating

Cover

- Chemivic (NBR/PVC)

Reinforcement

- Spiral wire between plies of synthetic fabric

Temperature Range

- 25°F / -32°C ~ 200°F / 93°C

Design Factor

- 4:1

Packaging

- Coroplast packaging. Also available on demand with heavy duty corrugated thermoplastic culvert packaging.

Coupling

- Built-in coupling with flange. Unless specified , flanges are supplied with 150#RFSO ANSI-B16.5 / ASTM A105

Branding

CONTINENTAL FLEXDOCK 225 PSI WP NITRILE VERSAFUEL MADE IN CANADA

FLEXDOCK VERSAFUEL

Order Codes: 541-119

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
4	101.60	5.21	132.42	39.37	Black	15.00	381.00	29.00	736.60	225	1.55	302.98	450.88	21111611
6	152.40	7.35	186.58	24.61	Black	22.00	558.80	29.00	736.60	225	1.55	392.05	583.44	21111610
				32.83	Black	22.00	558.80	29.00	736.60	225	1.55	476.54	709.16	20917380
				15.09	Black	30.00	762.00	29.00	736.60	225	1.55	366.56	545.49	21111588
				30	Black	30.00	762.00	29.00	736.60	225	1.55	18.40	27.38	21116686
8	203.40	9.33	237.06	30	Black	30.00	762.00	29.00	736.60	225	1.55	551.95	821.39	21148988
				32.83	Black	30.00	762.00	29.00	736.60	225	1.55	586.87	873.36	20961277
				36.08	Black	30.00	762.00	29.00	736.60	225	1.55	627.56	933.91	21025080
				39.33	Black	30.00	762.00	29.00	736.60	225	1.55	668.02	994.12	21025082
12	305.44	13.61	345.66	60	Black	30.00	762.00	29.00	736.60	225	1.55	12.44	18.51	20783455
12	305.44	13.61	345.66	30	Black					225	1.55	34.08	50.71	21116687