

FLEXSTEEL® FUTURA™ E25

Flexsteel® Futura™ E25 is designed for dispensing applications with ethanol blends up to 25%. This assembly provides the quality Futurin™ cover with its superior ozone resistance. It is UL Approved to UL330 / UL330A.

Performance + Specs

Tube NITRILE (NBR)	Cover FUTURIN™ Synthetic Rubber
Reinforcement One braid steel wire	Temperature Range -40°F / -40°C ~ 140°F / 60°C
Design Factor 4:1	Packaging Available in factory coupled assemblies only.
Coupling Zinc Alloy, 3/4" & 1" NPT Threads	

Branding

Continental ContiTech 3/4" (UL) Flexsteel® Futura™ E25 Made in U.S.A.

FLEXSTEEL® FUTURA™ E25

Order Codes: 532-336

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.10	1.13	28.70	0.67	Orange	50	0.34	1.36	2.02	20926092
				0.75	Orange	50	0.34	1.40	2.08	20924437
				8	Orange	50	0.34	5.32	7.92	20926093
				8.5	Orange	50	0.34	5.55	8.25	20917162
				9	Orange	50	0.34	5.77	8.59	20916862
1	25.40	1.38	35.05		Orange	50	0.34	0.63	0.94	21221111
				0.67	Orange	50	0.34	1.21	1.80	21221181
				0.75	Orange	50	0.34	1.13	1.68	21221180
				8	Orange	50	0.34	5.87	8.73	21221048
				8.5	Orange	50	0.34	6.16	9.17	21221182
				9	Orange	50	0.34	6.45	9.60	21221047