

Continental  FLEXSTEEL® FUTURA™ HVR Low Perm (10g/r

FLEXSTEEL® FUTURA™ HVR LOW PERM

Flexsteel® Futura™ HVR Low Perm features an abuse-resistant cover compound with enhanced ozone resistance for service longevity. Meets UL330, CARB, ORVR and EVR requirements. Factory-made assemblies with fittings designed for Healy Stage II Enhanced Vapor Recovery (EVR) Systems compatibility. Low permeation, less than 10g/m2/day

Performance + Specs

Tube Nitrile (NBR) Fluorothermoplastic Barrier	Cover Futurin™ (ORS)
Reinforcement One Braid Steel Wire	Temperature Range -40°F / -40°C ~ 140°F / 60°C
Packaging Coupled lengths only, 6 pieces per box	Coupling Available as factory coupled assemblies only.
Non Stock / Sizes For special production run minimum requirements, contact customer service	

Branding

Continental 558N 3/4" RU Flexsteel Futura HVR Low Perm (10g/m2/day) Gasoline Hose Made in USA

Flexsteel® Futura™ HVR Low Perm

Order Codes: 532-330

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
				6	Black	50	0.34	5.16	7.67	20615329
3/4	19.10	1.13	28.70	6	Black	50	0.34	3.93	5.85	20801407
				8	Black	50	0.34	6.32	9.41	20615364