



FLEXSTEEL® FUTURA™ LOW PERM

The Flexsteel® Futura™ Low Perm dispensing hose offers superior, long-lasting service with multi-fuel capability. This hose is designed for use at filling stations to reduce permeation rates to 10 grams/m²/day and improve air quality and emissions. Premium abuse-resistant cover compound with enhanced ozone resistance for service longevity. Meets UL330 requirements. Meets stringent permeation requirements of less than 10 grams/m²/day.

Performance + Specs

Tube Nitrile (NBR) Fluorothermoplastic Barrier	Cover Futurin™ (ORS)
Reinforcement One braid steel wire	Temperature Range -40°F / -40°C ~ 140°F / 60°C
Packaging Coupled lengths only, 10 pieces per box.	Coupling Available as factory coupled assemblies only.

Branding

Continental 559N Made in USA 3/4" Flexsteel® Futura™ Low Perm (10g/m2/day) Gasoline Hose

Flexsteel® Futura™ Low Perm

Order Codes: 532-338

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.10	1.14	28.96	8.6	Black	50	0.34	5.17	7.69	20754820