

FLEXTRA LW

Used by tank trucks, bulk petroleum stations, and others to transfer ethanol blends and petroleum products under pressure, suction and/or gravity flow. Flexible and lightweight to provide excellent service. Not recommended where aromatic content exceeds 50%.

Performance + Specs

Tube

- NITRILE (NBR)

Reinforcement

- Spiral-Plied fabrics with double wire helix

Temperature Range

- -40°F / -40°C ~ 180°F / 82°C

Design Factor

- 4:1

Packaging

- Wrapped, Coiled and Palletized

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Branding

CONTINENTAL LW BLACK FLEXTRA 150 PSI WP MADE IN CANADA

Flextra LW

Order Codes: 543-787

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/4	31.75	1.73	44.01	100	Black	2.50	63.50	29.00	736.60	150	1.03	0.77	1.15	20099241
1-1/2	38.10	1.99	50.44	100	Black	3.00	76.20	29.00	736.60	150	1.03	0.93	1.38	20099242
2	50.80	2.48	63.09	100	Black	4.00	101.60	29.00	736.60	150	1.03	1.17	1.74	20099243
2-1/2	63.50	3.04	77.15	100	Black	6.00	152.40	29.00	736.60	150	1.03	1.63	2.42	20106005
3	76.20	3.54	89.84	100	Black	7.50	190.50	29.00	736.60	150	1.03	1.92	2.85	20099244
4	101.60	4.57	116.02	100	Black	10.00	254.00	29.00	736.60	150	1.03	2.74	4.08	20099245