



FLEXWING® FLOSYN

Continental Flexwing® is a versatile chemical hose capable of handling a wide variety of acids, alcohols, salt solutions and petroleum-based products.

Performance + Specs

Tube Flosyn® Rubber	Cover - Nitrile / PVC Blend - Wrapped Finish
Reinforcement - Spiral-Plied Synthetic Fabric - Double Wire Helix	Temperature Range -25°F / -32°C ~ 250°F / 121°C
Design Factor 4:1	Packaging Coiled & Poly-Wrapped
Coupling Refer to the Continental Industrial Hose Assembly Manual for crimp specifications.	

Branding

Continental Flexwing® with Flosyn® 150 PSI WP

Flexwing® Flosyn

Order Codes: 541-063

Product Numbers																
ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.05	1.34	34.04	100	Black	600	4.14	3.00	76.20	29.00	736.60	150	1.03	0.68	1.01	20014911
1	25.40	1.49	37.96	100	Black	600	4.14	3.50	88.90	29.00	736.60	150	1.03	0.69	1.03	20014912
1-1/2	38.10	2.04	51.73	100	Black	600	4.14	4.50	114.30	29.00	736.60	150	1.03	1.08	1.61	20014915
2	50.80	2.58	65.66	50	Black	600	4.14	6.00	152.40	29.00	736.60	150	1.03	1.50	2.23	20014916
				100	Black	600	4.14	6.00	152.40	29.00	736.60	150	1.03	1.50	2.23	20014917
4	101.60	4.81	122.13	50	Black	600	4.14	12.00	304.80	29.00	736.60	150	1.03	4.00	5.95	20014920
				100	Black	600	4.14	12.00	304.80	29.00	736.60	150	1.03	4.00	5.95	20014921
6	152.40	6.95	176.60	100	Black	600	4.14	30.00	762.00	29.00	736.60	150	1.03	7.36	10.95	20131037