



FLEXWING® VERSAFUEL

Continental Flexwing Versafuel is for use in tank truck and in-plant operation to transfer diesel, biodiesel blends, B-100, ethanol blends, gasoline, oil and petroleum base products up to 60% aromatic content.

Performance + Specs

Tube

- Specially Compounded Nitrile (static dissipating)
- ARPM Class A (High Oil Resistance)

Cover

- Synthetic Rubber
- ARPM Class A (High Oil Resistance)

Reinforcement

- Spiral-Plied Synthetic Fabric
- Double Wire Helix

Temperature Range

- -30°F / -34°C ~ 180°F / 82°C

Design Factor

- 4:1

Packaging

- 100ft lengths, Coiled & Poly-Wrapped

Coupling

- Refer to the Continental Industrial Hose Assembly Manual for crimp specifications.

Non Stock / Sizes

- 400' minimum order

Downloads

- [Alternative Fuel Compatibility \(Tubes & Covers\)](#)

Branding

Continental Flexwing VersaFuel™ 150 PSI WP

Flexwing® Versafuel

Order Codes: 543-422

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.48	37.66	100	Black	600	4.14	2.00	50.80	29.00	736.60	150	1.03	0.57	0.85	20339606
1-1/4	31.75	1.80	45.69	100	Black	600	4.14	3.00	76.20	29.00	736.60	150	1.03	0.81	1.21	20339625
1-1/2	38.10	2.05	52.08	100	Black	600	4.14	4.00	101.60	29.00	736.60	150	1.03	0.96	1.42	20339626
2	50.80	2.55	64.82	100	Black	600	4.14	5.00	127.00	29.00	736.60	150	1.03	1.24	1.85	20339628
2-1/4	57.15	2.82	71.69	100	Black	600	4.14	5.50	139.70	29.00	736.60	150	1.03	1.46	2.18	20465625
2-1/2	63.50	3.07	78.03	100	Black	600	4.14	6.00	152.40	29.00	736.60	150	1.03	1.61	2.39	20339627
3	76.20	3.60	91.44	100	Black	600	4.14	8.00	203.20	29.00	736.60	150	1.03	2.03	3.03	20339629
4	101.60	4.60	116.82	100	Black	600	4.14	12.00	304.80	29.00	736.60	150	1.03	2.63	3.92	20339650