



FUEL DISCHARGE

Fuel Discharge hose is for the discharge of gasoline, oil, ethanol blends and other petroleum based products up to 50% aromatic content in tank and industrial applications.

Performance + Specs

Tube

- Nitrile (NBR)
- ARPM Class A (High Oil Resistance)

Cover

- Nitrile / PVC Blend
- ARPM Class A (High Oil Resistance)

Reinforcement

- Spiral-Plied Synthetic Fabric With Antistatic Wire

Temperature Range

- -35°F / -37°C ~ 180°F / 82°C

Design Factor

- 4:1

Packaging

- Coiled and polywrapped, cut length check with ContiTech

Coupling

- Refer to the Continental Industrial Hose Assembly Manual for crimp specifications.

Branding

CONTINENTAL FUEL DISCHARGE 150 MAX WP MADE IN CANADA

Fuel Discharge

Order Codes: 543-331, 543-057

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.05	1.16	29.41	100	Black	600	4.14	29.00	736.60	150	1.03	0.37	0.55	20032339
1	25.40	1.41	35.76	100	Black	600	4.14	29.00	736.60	150	1.03	0.46	0.68	20032357
				400	Black	600	4.14	29.00	736.60	150	1.03	0.46	0.68	20274945
1-1/4	31.75	1.66	42.11	100	Black	600	4.14	29.00	736.60	150	1.03	0.55	0.82	20050546
				400	Black	600	4.14	29.00	736.60	150	1.03	0.55	0.82	20273551
1-1/2	38.10	1.91	48.46	100	Black	600	4.14	29.00	736.60	150	1.03	0.64	0.95	20017756
				400	Black	600	4.14	29.00	736.60	150	1.03	0.64	0.95	20273552
1-3/4	45.08	2.18	55.44	100	Black			29.00	736.60	150	1.03	0.74	1.10	20050565
2	50.80	2.43	61.60	100	Black	600	4.14	29.00	736.60	150	1.03	0.86	1.28	20017758
				400	Black	600	4.14	29.00	736.60	150	1.03	0.86	1.28	20017761
2	50.80	2.60	66.00	100	Black	1200	8.27	29.00	736.60	300	2.07	1.23	1.83	20582824
				200	Black	1200	8.27	29.00	736.60	300	2.07	1.23	1.83	20827875
2-1/2	63.50	2.93	74.30	100	Black	600	4.14	29.00	736.60	150	1.03	1.05	1.56	20032358
				400	Black	600	4.14	29.00	736.60	150	1.03	1.05	1.56	20116324
2-3/4	70.10	3.21	81.54	394	Black			29.00	736.60	150	1.03	1.23	1.82	20768046
3	76.20	3.45	87.64	100	Black	600	4.14	29.00	736.60	150	1.03	1.32	1.97	20017764
				200	Black	600	4.14	29.00	736.60	150	1.03	1.32	1.97	20263499
				400	Black	600	4.14	29.00	736.60	150	1.03	1.32	1.97	20017765
3	76.20	3.65	92.68	100	Black	1200	8.27	29.00	736.60	300	2.07	1.94	2.88	20582825
3-1/2	89.92	3.99	101.36	100	Black	600	4.14	29.00	736.60	150	1.03	1.54	2.30	20050547
4	101.60	4.45	113.04	100	Black	600	4.14	29.00	736.60	150	1.03	1.73	2.57	20017767
				400	Black	600	4.14	29.00	736.60	150	1.03	1.73	2.57	20017769
4	101.60	4.65	118.08	100	Black	1200	8.27	29.00	736.60	300	2.07	2.52	3.74	20582826
5	127.00	5.54	140.60	100	Black	600	4.14	29.00	736.60	150	1.03	2.49	3.71	20821525
6	152.40	6.59	167.28	100	Black	600	4.14	29.00	736.60	150	1.03	3.29	4.90	20126041
				200	Black	600	4.14	29.00	736.60	150	1.03	3.29	4.90	20238034
				400	Black	600	4.14	29.00	736.60	150	1.03	3.29	4.90	20267062
6	152.40	6.79	172.56	100	Black	1200	8.27	29.00	736.60	300	2.07	4.54	6.75	20582827