

GEN PETRO TANK TRUCK CORR

Performance + Specs

Tube Nitrile (NBR)	Cover Styrene-Butadiene (SBR) and Natural Rubber (NR)
Reinforcement Spiral-Plied Fabric, Wire Helix	Temperature Range -25°F / -32°C ~ 180°F / 82°C
Design Factor 4:1	Packaging 100' lengths, coiled and polywrapped
Coupling Contact fitting manufacturer for proper fitting recommendation and coupling procedure.	

Branding

TANK TRUCK PETROLEUM TRANSFER 150 PSI MAX WP "MADE IN CANADA

GEN Petro Tank Truck Corr

Order Codes: 543-149

Product Numbers														
ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
2	50.80	2.39	60.66	100	Red	5.00	127.00	29.00	736.60	150	1.03	0.91	1.35	21125239
3	76.20	3.52	89.39	100	Red	7.00	177.80	29.00	736.60	150	1.03	1.81	2.70	21125242
4	101.60	4.57	115.98	100	Red	10.00	254.00	29.00	736.60	150	1.03	2.62	3.90	21125243