

GENERIC LOW TEMP TANK TRUCK

For the transfer of gasoline and other petroleum based products under pressure, gravity flow or full suction where a low temperature rating is desired.

Performance + Specs

Tube Nitrile (NBR)	Cover SBR
Reinforcement Spiral-Plied fabrics with dual steel helix wire	Temperature Range -50°F / -46°C ~ 180°F / 82°C
Design Factor 4:1	Packaging Coiled & Poly-Wrapped
Coupling Contact fitting manufacturer for proper fitting recommendation and coupling procedure.	

Branding

LOW TEMPERATURE PETROLEUM TANK TRUCK 150 PSI WP MADE IN CANADA

Generic Low Temp Tank Truck

Order Codes: 543-633

Product Numbers														
ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/2	38.10	2.00	50.80	400	Blue	4.00	101.60	29.00	736.60	150	1.03	0.89	1.32	20949784
2	50.80	2.50	63.50	100	Blue	5.00	127.00	29.00	736.60	150	1.03	1.14	1.69	20476866
				400	Blue	5.00	127.00	29.00	736.60	150	1.03	1.15	1.71	20620364
2-1/2	63.50	3.01	76.53	400	Blue	7.00	177.80	29.00	736.60	150	1.03	1.48	2.20	20949785
3	76.20	3.55	90.24	100	Blue	7.50	190.50	29.00	736.60	150	1.03	1.87	2.79	20476867
				400	Blue	7.50	190.50	29.00	736.60	150	1.03	1.87	2.79	20620365
4	101.60	4.57	116.10	100	Blue	10.00	254.00	29.00	736.60	150	1.03	2.62	3.90	20476868