

GENERIC

Designed for use in low-temperature operation for the transfer of gasoline, oil, and other petroleum products.

Performance + Specs

Tube Nitrile (NBR)	Cover SYNTHETIC RUBBER
Reinforcement Spiral-Plied synthetic fabric with spiral grounding wire	Temperature Range -65°F / -54°C ~ 180°F / 82°C
Design Factor 4:1	Coupling Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Branding

LOW TEMPERATURE FUEL DISCHARGE A.S. MADE IN CANADA

Generic
Order Codes: 543-654 (150 PSI)

Product Numbers												
ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
2	50.80	2.49	63.20	400	Blue	29.00	736.60	150	1.03	0.96	1.42	20069585
3	76.20	3.51	89.24	100	Blue	29.00	736.60	150	1.03	1.46	2.17	20733034
4	101.60	4.51	114.64	100	Blue	29.00	736.60	150	1.03	1.90	2.83	20018014
				400	Blue	29.00	736.60	150	1.03	1.90	2.83	21054308