

GORILLA®

Gorilla® is a Premium Quality, multipurpose industrial hose with a wide range of applications in factories, construction, agriculture, quarries, mines, railroads, the oil and gas industry and shipbuilding . All sizes are rated at 500 psi (3 .4 MPa) maximum working pressure. The premium Carbryn™ cover offers the most superior abrasion resistance of air and multipurpose hoses. Non-conductive, minimum electrical resistance greater than 1 megohm per inch of hose length at 1000 Volts DC.

Performance + Specs

Tube

- Nitrile (NBR)
- ARPM Class A (High Oil Resistance)

Cover

- Carbryn™
- ARPM Class A (High Oil Resistance)
- MSHA Approved

Reinforcement

- Spiral Flexten® Yarn
- 2" is Braided Synthetic Yarn

Temperature Range

- -20°F / -29°C ~ 210°F / 99°C

Design Factor

- 4:1

Packaging

- 3/16" to 3/4" - 500ft Reels
- 1" - 450ft Reels
- 1-1/4" - 250ft to 400ft Reels
- 1-1/2" - 150ft to 300ft Reels
- 2" - 2 Pieces, 100ft each Box
- Max. 3 Pieces, 50ft Increments

Coupling

- *Refer to the Continental Industrial Hose Assembly Manual for crimp specifications.
- Coupled assemblies available.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

Gorilla® 1" (25.4 mm) 500 PSI. Made in USA. Continental Flame Resistant USMSHA No. 2G-IC-14C/39

Gorilla®

Order Codes: 536-446 (2 Inch), 569-035 (1/4" to 1-1/2")

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1/4	6.40	0.61	15.40	25	Yellow	2000	13.79	3.00	76.20	500	3.45	3.62	5.39	20129563
				50	Yellow	2000	13.79	3.00	76.20	500	3.45	7.25	10.79	20132763
				500	Yellow	2000	13.79	3.00	76.20	500	3.45	0.14	0.22	20026239
3/8	9.50	0.73	18.60	25	Yellow	2000	13.79	4.50	114.30	500	3.45	4.68	6.96	20129566
				50	Yellow	2000	13.79	4.50	114.30	500	3.45	9.35	13.91	20132764
				500	Yellow	2000	13.79	4.50	114.30	500	3.45	0.19	0.28	20026256
1/2	12.70	0.89	22.60	25	Yellow	2000	13.79	6.00	152.40	500	3.45	5.98	8.89	20129569
				50	Yellow	2000	13.79	6.00	152.40	500	3.45	11.95	17.78	20132766
				500	Yellow	2000	13.79	6.00	152.40	500	3.45	0.24	0.36	20026273
5/8	15.90	1.06	27.00	500	Yellow	2000	13.79	7.50	190.50	500	3.45	0.32	0.48	20026289
3/4	19.10	1.18	30.00	50	Yellow	2000	13.79	9.00	228.60	500	3.45	18.65	27.75	20129582
				500	Yellow	2000	13.79	9.00	228.60	500	3.45	0.37	0.56	20026290
1	25.40	1.49	37.80	450	Yellow	2000	13.79	12.00	304.80	500	3.45	0.53	0.79	20026304
1-1/4	31.80	1.80	45.60	400	Yellow	2000	13.79	15.00	381.00	500	3.45	0.72	1.07	20026306
1-1/2	38.10	2.04	51.80	300	Yellow	2000	13.79	18.00	457.20	500	3.45	0.82	1.22	20026309
2	50.80	2.62	66.55	50	Yellow	2000	13.79	24.00	609.60	500	3.45	1.36	2.03	20305356
				100	Yellow	2000	13.79	24.00	609.60	500	3.45	1.36	2.03	20023183