



GUNITE

For the efficient transfer of sand and cement to the placement mixing gun nozzle. Recommended for all types of gunning applications.

Performance + Specs

Tube

- 549863 CHemituf Tan
- 549862 - Natural Rubber Tan
- 549865- Natural Rubber Blk, antistatic wire
- 549654 Conticlean Survivor BLK
- 549233 Conticlean Survivor Tan

Cover

- SBR

Reinforcement

- Spiral-plied synthetic fabric

Temperature Range

- -40°F / -40°C ~ 180°F / 82°C

Design Factor

- 4:1

Packaging

- Coiled & Poly-Wrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

- For special production run minimum requirements, Contact Customer Service.

Branding

Gunite 150 Max WP

Gunite

Order Codes: 549-862 549-862 (Tan Pureten), 549-865 (Black Pureten, Anti-static Wire), 549-863 (Chemituf), 549-865 549-862 (Tan Pureten), 549-865 (Black Pureten, Anti-static Wire), 549-863 (Chemituf), 549-863 549-862 (Tan Pureten), 549-865 (Black Pureten, Anti-static Wire), 549-863 (Chemituf)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/2	38.10	2.43	61.70	50	Brown	600	4.14	150	1.03	1.49	2.22	20020274
1-1/2	38.10	2.32	58.90	50	Black	600	4.14	150	1.03	1.20	1.79	20020287
1-5/8	41.50	2.58	65.50	50	Brown	600	4.14	150	1.03	1.63	2.42	20020277
1-5/8	41.50	2.50	63.50	50	Black	600	4.14	150	1.03	1.37	2.04	20020290
1-3/4	45.08	2.70	68.68	50	Brown	600	4.14	150	1.03	1.69	2.52	20020278
2	50.80	2.93	74.40	50	Brown	600	4.14	150	1.03	1.86	2.77	20020279
2-1/2	63.50	3.44	87.42	50	Brown	600	4.14	150	1.03	2.25	3.35	20962541
				50	Brown			150	1.03	2.41	3.58	20020285