



HARDWALL MARINE WET EXHAUST J2006

Suitable for water suction and discharge applications including engine intake, bilge exhaust, toilet, holding tank, and scupper lines. Also ideal for industrial water transfer where unique sizing is needed to fit over pipe. Complies with SAE J2006 R2 specifications.

Performance + Specs

Tube

- Synthetic Rubber (SBR)
- ARPM Class B (Medium Oil Resistance)

Cover

- SBR synthetic rubber (wrapped impression)

Reinforcement

- Spiral-Plied Synthetic Fabric
- Wire helix

Temperature Range

- -25°F / -32°C ~ 180°F / 82°C

Design Factor

- 4:1

Packaging

- 1/2" - 5" – 50ft Exact length, Coiled & Poly-Wrapped
- 6" - 8" – 25ft Exact length, Poly-Wrapped

Coupling

- Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Non Stock / Sizes

- For special production run minimum requirements, see Appendix D.

Branding

CONTINENTAL ELITE HARDWALL MARINE WET EXHAUST SAE J2006 R2 (YEAR) MADE IN CANADA

Hardwall Marine Wet Exhaust J2006

Order Codes: 542-812

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
5/8	16.05	0.98	24.95	50	Black	800	5.52	2.00	50.80	29.00	736.60	200	1.38	0.28	0.42	20025366
3/4	19.05	1.10	27.95	50	Black	800	5.52	3.00	76.20	29.00	736.60	200	1.38	0.34	0.50	20032166
7/8	22.23	1.19	30.33	50	Black	800	5.52	3.00	76.20	29.00	736.60	200	1.38	0.34	0.51	20030073
1-1/8	28.58	1.44	36.68	50	Black	600	4.14	4.00	101.60	29.00	736.60	150	1.03	0.43	0.63	20016947
1-1/4	31.75	1.57	39.84	50	Black	600	4.14	4.00	101.60	29.00	736.60	150	1.03	0.47	0.69	20016948
1-5/16	33.00	1.62	41.09	50	Black	600	4.14	4.00	101.60	29.00	736.60	150	1.03	0.48	0.72	20016949
1-3/8	35.00	1.70	43.09	50	Black	500	3.45	4.00	101.60	29.00	736.60	125	0.86	0.51	0.76	20030074
1-1/2	38.10	1.87	47.39	50	Black	500	3.45	4.00	101.60	29.00	736.60	125	0.86	0.62	0.93	20016950
1-5/8	41.50	2.00	50.83	50	Black	400	2.76	4.00	101.60	29.00	736.60	100	0.69	0.69	1.03	20016951
1-3/4	45.08	2.14	54.41	50	Black	400	2.76	4.00	101.60	29.00	736.60	100	0.69	0.74	1.11	20016952
1-7/8	47.63	2.24	56.96	50	Black	400	2.76	6.00	152.40	29.00	736.60	100	0.69	0.78	1.16	20016953
2	50.80	2.40	61.02	50	Black	400	2.76	6.00	152.40	29.00	736.60	100	0.69	0.94	1.40	20016954
				400	Black	400	2.76	6.00	152.40	29.00	736.60	100	0.69	0.94	1.40	20288523
2-1/8	53.98	2.50	63.45	50	Black	300	2.07	6.00	152.40	29.00	736.60	75	0.52	0.94	1.40	20016955
2-1/4	57.15	2.62	66.62	50	Black	300	2.07	6.00	152.40	29.00	736.60	75	0.52	0.99	1.48	20016956
2-3/8	60.77	2.77	70.24	50	Black	300	2.07	8.00	203.20	29.00	736.60	75	0.52	1.05	1.56	20016957
2-1/2	63.50	2.87	72.97	50	Black	300	2.07	8.00	203.20	29.00	736.60	75	0.52	1.10	1.63	20016958
2-3/4	70.10	3.31	83.97	50	Black	200	1.38	8.00	203.20	29.00	736.60	50	0.34	1.75	2.60	20016960
2-7/8	73.28	3.43	87.15	50	Black	200	1.38	8.00	203.20	29.00	736.60	50	0.34	1.82	2.72	20016961
3	76.20	3.55	90.07	50	Black	200	1.38	10.00	254.00	29.00	736.60	50	0.34	1.89	2.82	20016962
3-1/8	79.40	3.67	93.27	50	Black	200	1.38	10.00	254.00	29.00	736.60	50	0.34	1.97	2.93	20016963
3-1/2	89.92	4.09	103.79	50	Black	200	1.38	10.00	254.00	29.00	736.60	50	0.34	2.20	3.28	20016965
4	101.60	4.63	117.61	50	Black	200	1.38	12.00	304.80	29.00	736.60	50	0.34	2.96	4.40	20016966
4-1/2	114.30	5.17	131.27	50	Black	200	1.38	14.00	355.60	29.00	736.60	50	0.34	3.47	5.17	20016968
5	127.00	5.75	145.95	25	Black	200	1.38	24.00	609.60	29.00	736.60	50	0.34	4.60	6.85	20016969
6	152.40	6.75	171.44	25	Black	200	1.38	30.00	762.00	29.00	736.60	50	0.34	5.58	8.31	20016973