

HD AIR 300

A versatile, air hose for use in rough industrial applications or for severe service in mines, quarries and construction jobs.

Performance + Specs

Tube EPDM	Cover EPDM
Reinforcement Spiral Textile Reinforcement	Temperature Range -40°F / -40°C ~ 220°F / 104°C
Design Factor 4:1	Packaging Coiled & Polywrapped
Coupling Contact fitting manufacturer for proper fitting recommendation and coupling procedure.	

Branding

CONTINENTAL AIR 300 PSI WP EPDM MADE IN CANADA

HD AIR 300

Order Codes: 549-819 Blue, 549-820 Red

Product Numbers												
ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
3/4	19.05	1.30	33.05	400	Blue	1200	8.27	300	2.07	0.50	0.75	20702431
				400	Red	1200	8.27	300	2.07	0.50	0.75	20702432
1	25.40	1.55	39.40	400	Blue	1200	8.27	300	2.07	0.62	0.93	20697247
				400	Red	1200	8.27	300	2.07	0.62	0.93	20697320
1-1/4	31.75	1.80	45.75	400	Blue	1200	8.27	300	2.07	0.75	1.11	20671979
				400	Red	1200	8.27	300	2.07	0.74	1.11	20672061