



HD VACUUM

Continental HD Vacuum has heavy-duty construction for handling abrasive particles from metal, rock and marble grinding machines under vacuum. Its lightweight construction can be used to exhaust fumes and abrasive dust from woodworking machines, metal, rock, granite and similar processing equipment.

Performance + Specs

Tube

- Chemituf®
- Static Dissipating / Static Conductive

Cover

- SBR (Corrugated)

Reinforcement

- Spiral-Plid Fabric
- Wire Helix

Temperature Range

- -25°F / -32°C ~ 180°F / 82°C

Packaging

- Coiled & Poly-Wrapped

Coupling

- Refer to the Continental Industrial Hose Assembly Manual for crimp specifications.

Non Stock / Sizes

- Custom lengths available. Available with Black Pureten™

Branding

CONTINENTAL HD VACUUM MADE IN CANADA

HD Vacuum

Order Codes: 549-208 (6" & Below), 541-208 (8" ID)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1-1/4	31.75	1.71	43.43	50	Black	5.00	127.00	29.00	736.60	50	0.34	0.65	0.97	20019381
1-1/2	38.10	1.98	50.23	300	Black	6.00	152.40	29.00	736.60	50	0.34	0.81	1.20	20478839
2	50.80	2.48	62.93	50	Black	8.00	203.20	29.00	736.60	50	0.34	1.03	1.54	20019384
8	203.40	8.87	225.29	50	Black	48.00	1,219.20	29.00	736.60	25	0.17	8.22	12.23	20015105
				100	Black	48.00	1,219.20	29.00	736.60	25	0.17	8.22	12.23	20355374