

HD WATER SD

A heavy duty, all-purpose water suction and discharge hose.

Performance + Specs

Tube SBR	Cover SBR
Reinforcement Spiral-Plied Fabric, Wire Helix	Temperature Range -25°F / -32°C ~ 180°F / 82°C
Design Factor 4:1	Packaging 1" to 3" Coiled or straight, polywrapped 4" to 14" Straight, polywrapped
Coupling Factory Assemblies Available or contact fitting manufacturer for proper fitting recommendation and coupling procedure, the larger diameters are suitable for built-in steel nipple flanges.	

Branding

CONTINENTAL MADE IN CANADA

HD Water SD

Order Codes: 541-322 (6"-19"), 542-322 (1"-6")

Product Numbers																
ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
1	25.40	1.54	39.22	50	Black			3.00	76.20			300	2.07	0.71	1.06	20029739
1-1/2	38.10	2.08	52.80	50	Black			4.50	114.30			300	2.07	1.08	1.61	20029750
2-1/2	63.50	3.11	79.07	100	Black			9.00	228.60			300	2.07	1.76	2.61	20016540
3	76.20	3.65	92.59	100	Black			12.00	304.80			300	2.07	2.29	3.41	20016541
4	101.60	4.72	119.83	50	Black			16.00	406.40	29.00	736.60	300	2.07	3.35	4.99	20943437
				100	Black			16.00	406.40			300	2.07	3.32	4.93	20263140
				200	Black			16.00	406.40			300	2.07	3.32	4.93	20344419
6	152.40	7.01	178.12	100	Black	900	6.21	24.00	609.60	29.00	736.60	300	2.07	7.56	11.25	20846022