

HOT AIR LINER SW

This humidification Hot Air solution is engineered for controlled moisture injection into heated air streams. The system is designed to stabilize humidity levels in hot air applications while preventing condensation, hose degradation, or process inconsistency. It is particularly suited transporting hot air from the compressor to tanks on bulk transport vehicles, for dry material.

Performance + Specs

Tube

- High Temperature EPDM (Black)

Cover

- High Temperature EPDM (Black)

Reinforcement

- Spiral-Plied Fabrics

Temperature Range

- -40°F / -40°C ~ 356°F / 180°C

Design Factor

- 4:1

Packaging

- Coiled, Wrapped and Palletized

Coupling

- (Discharge Black Tube)

Branding

CONTINENTAL BLACK HOT AIR HOSE 180°C MAX MADE IN CANADA

Hot Air Liner SW

Order Codes: 549-761 Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
2	50.80	2.66	67.52	131.17	Black	200	1.38	158.96	236.56	20620556
2-3/8	60.77	3.00	76.29	131.17	Black	200	1.38	176.94	263.31	20620557
2-1/2	63.50	3.25	82.62	131.17	Black	200	1.38	226.63	337.27	20620558
3	76.20	3.74	95.00	131.17	Black	200	1.38	259.50	386.18	20620559