



HOT SULFUR

Designed for the transfer of hot molten sulfur in tank truck application, all sizes rated at full vacuum.

Performance + Specs

Tube Butyl (IIR)	Cover EPDM (Wrapped Finish)
Reinforcement - Spiral-Plied Aramid Fibers - Wire Helix	Temperature Range -25°F / -32°C ~ 325°F / 163°C
Design Factor 4:1	Packaging Coiled & Poly-Wrapped
Coupling Contact fitting manufacturer for proper fitting recommendation and couple procedure.	

Branding

CONTINENTAL HOT SULFUR SERVICE 200 PSI WP 325 F MAX MADE IN CANADA

Hot Sulfur
Order Codes: 541-688

Product Numbers																
ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Min. Burst (PSI)	Min. Burst (Mpa)	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
2	50.80	2.75	69.92	100	Black	800	5.52			29.00	736.60	200	1.38	1.64	2.43	20901199
3	76.20	3.83	97.36	100	Black	800	5.52	15.00	381.00	29.00	736.60	200	1.38	2.60	3.87	20156103
4	101.60	4.71	119.53	100	Black	800	5.52	20.00	508.00	29.00	736.60	200	1.38	2.84	4.22	20488749