



HOT TAR & ASPHALT

Designed for petroleum-based products up to 350°F between docks and tankers or barges under heavy-duty conditions.

Performance + Specs

Tube

- Nitrile (NBR)
- Flat Steel Wire for Support

Cover

- Chloroprene (CR)

Reinforcement

- Spiral-Plied Synthetic Fabric
- with Wire Helix

Temperature Range

- -25°F / -32°C ~ 350°F / 177°C

Design Factor

- 4:1

Packaging

- Custom lengths available, contact customer service.

Coupling

- Coupled with galvanized built-in steel nipple/150#RFISO flanges. Available in other bolt hole patterns, materials and floating flanges on request. Smooth bore assembly is electrically continu

Non Stock / Sizes

- Custom lengths available, contact customer service.

Branding

Continental RB Dock Hot Asphalt, 350°F 225 PSI max

Hot Tar & Asphalt

Order Codes: 541-606 (Smooth Bore)

Product Numbers

ID (in)	ID (mm)	Nom. OD (in.)	Nom. OD (mm)	Length (ft)	Color	Bend Radius (in.)	Bend Radius (mm)	Vacuum (in.)	Vacuum (mm)	WP (PSI)	WP (MPa)	Weight (lbs/ft)	Weight (kg/m)	Part Number
4	101.60	5.38	136.60	100	Black	36.00	914.40	29.00	736.60	225	1.55	7.06	10.51	20283279